

## PRODUCT BULLETIN

### MAKS 11293

#### GLUTARALDEHYDE 50%

##### PRINCIPAL USES

**MAKS 11293** is widely used for oil production, medical care, bio-chemical, leather treatment, tanning agents, protein cross-linking agent; in the preparation of heterocyclic compounds; also used for plastics, adhesives, fuels, perfumes, textile, paper making, printing; corrosion prevention of instruments and cosmetics etc.

##### PHYSICAL AND CHEMICAL PROPERTIES

Items	Index
Appearance	Transparent colorless or light yellow liquid
Assay %	25 Min
Ph value	3.1-4.5
Color	10 Max
Specific gravity	1.05-1.072
Methanol %	0.5 Max
Formaldehyde	No formaldehyde

##### DOSAGE & FEEDING

Your **BİMAKS** representative will recommend the optimum dosage necessary to ensure maximum program performance according to your specific system parameters.

**MATERIALS:** Storage and application equipments (pumps, lines) should be made of Stainless Steel, PE, PP, Fiberglass, PVC, Teflon, Viton or Buna-N. Do not use Aluminum, Brass, Copper, Copper Alloys, Hypalon, Neopren, Mils Steel or Nickel in contact with the neat product.

##### HANDLING-STORAGE-SHIPPING

As a standard precaution with all chemicals we recommend the use of personal protective equipments such as goggles and rubber gloves when handling. Consult the Material Safety Data Sheet as the only official source of Environmental and Safety information.

**MAKS 11293** can be stored for at least 24 months from date of shipping if kept in its original, unopened container and under normal warehouse conditions. Protect from freezing and from exposure to high temperature.

**MAKS 11293** is available in non-returnable containers of different sizes.

##### REMARKS

If you need assistance or more information on this product, please call 0 850 522 71 04. For more news about **BİMAKS** Company, visit our website at [www.bimaskimya.com.tr](http://www.bimaskimya.com.tr).