



# PRODUCT BULLETIN

## MAKS 9191

### DEMULSIFIER

#### GENERAL DESCRIPTION

**MAKS 9191** is based on inter-active substances and is applied as a demulsifier for the dehydration and desalting of crude oil.

#### PRINCIPAL USES

**MAKS 9191** is widely used in refinery dehydrating-desalting operations and particularly in desalting equipment. Particularly effective on high viscous and high sulphur content crude oils.

#### DOSAGE & FEEDING

Dosages may change according to the specific application and severity of the problem.

Your **BİMAKS** representative will recommend the optimum dosage necessary to ensure maximum program performance according to your specific system parameters.

MATERIALS: Storage and application equipments (pumps, lines) carbon and stainless steel, teflon. It should not be used with natural or butylic rubber, EPDM, polystyrene, polyethylene, polypropylene, PVC, polyvinylalcohols, polyacrylonitrile.

#### HANDLING-STORAGE-SHIPPING

As a standard precaution with all chemicals we recommend the use of personal protective equipments such as goggles and rubber gloves when handling. Consult the Material Safety Data Sheet as the only official source of Environmental and Safety information.

**MAKS 9191** can be stored for at least 24 months from date of shipping if kept in its original, unopened container and under normal warehouse conditions. Protect from freezing and from exposure to high temperature.

**MAKS 9191** is available in non-returnable containers of different sizes.

#### REMARKS

If you need assistance or more information on this product, please call 0 850 522 71 04. For more news about **BİMAKS** Company, visit our website at [www.bimakskimya.com.tr](http://www.bimakskimya.com.tr)